

# Challenger

SE R/T SRT8®

{ ENGINE & TRANSMISSION }

▶ 3.5L SOHC HIGH OUTPUT 24V	S	
■ V6 / 4-SPEED AUTOSTICK®		
▶ 5.7L HEMI® V8	0	
■ V8 / 6-SPEED MANUAL		
IncludesTRAK PAK Hill Start Assist, Anti-Spin Rear Axle, Bright Pedal Covers, Performance Steering, ESC Shutoff Switch"		
▶ 5.7L HEMI® V8 MULTI-DISPLACEMENT-SYSTEM	S	
■ V8 / 5-SPEED AUTOSTICK		
▶ 6.1L SRT® HEMI® V8		0
■ V8 / 6-SPEED MANUAL		
Includes TRAK PAK, Hill Start Assist, Anti-Spin Rear Axle, Bright Pedal Covers, Performance Steering, ESC Shutoff Switch		
▶ 6.1L SRT HEMI® V8		S
■ V8 / 5-SPEED AUTOSTICK		

# { MECHANICAL }

► ALTERNATOR			
■ 160 amp	S	S	S
▶ BATTERY			
■ 625 amp, maintenance free	S	S	S
▶ BRAKES	-		
4-wheel disc brakes	S		
Antilock 4-wheel disc HD brakes and all speed traction control	Р	S	
Available in Popular Equipment Package G on SE			
■ High-performance 4-wheel disc antilock with vented 14-inch front and 13.8-inch rear discs, in cludes Brembo® Performance 4-piston calipers and all speed traction control			S
► ENGINE COOLING			
■ Heavy Duty	S	S	
Severe Duty II			S

MECHANICAL CONT.	SE	R/T	SRT8
FUEL TANK			
18.5 gallon with tethered cap	S		
19 gallon with tethered cap		S	S
SPEED CONTROL			
Electronic with steering column-mounted controls	S	S	S
STEERING			
Power rack and pinion	S		
Performance		S	
Performance tuned	-		S
SUSPENSION			
Touring	S		
Performance		S	
High-performance			S
STABLIZER BAR			
Rear	S	S	S
TIP START			
Prevents ignition from over cranking  //A with manual transmission	\$	S	S
AXLE  Anti-spin differential rear axel (with manual transmission on R/T)		S	S
	{ <b>EX</b>	s TERIO	
	{ <b>EX</b>		
Anti-spin differential rear axel (with manual transmission on R/T)  ANTENNA	_	TERIO	<b>R</b> }
Anti-spin differential rear axel (with manual transmission on R/T)  ANTENNA Integrated into rear window	_	TERIO	<b>R</b> }
Anti-spin differential rear axel (with manual transmission on R/T)  ANTENNA Integrated into rear window  BADGING / STRIPES	S	<b>TERIO</b>	<b>R</b> }
Anti-spin differential rear axel (with manual transmission on R/T)  ANTENNA Integrated into rear window  BADGING / STRIPES  Challenger	S	TERIO S	<b>R</b> }
Anti-spin differential rear axel (with manual transmission on R/T)  ANTENNA Integrated into rear window  BADGING / STRIPES  Challenger  R/T	S	TERIO S	<b>R</b> }
Anti-spin differential rear axel (with manual transmission on R/T)  ANTENNA Integrated into rear window  BADGING / STRIPES  Challenger  R/T  SRT8®  Hemi® badge  SRT® Stripe Kit	S	TERIO S S	<b>R</b> }
ANTENNA Integrated into rear window  BADGING / STRIPES  Challenger  R/T  SRT8®  Hemi® badge  SRT® Stripe Kit  R/T hood to fender stripes	S	TERIO S S	<b>R</b> }  S  S  S
Anti-spin differential rear axel (with manual transmission on R/T)  ANTENNA Integrated into rear window  BADGING / STRIPES  Challenger  R/T  SRT8®  Hemi® badge  SRT® Stripe Kit	S	TERIO S S S S	<b>R</b> }
ANTENNA Integrated into rear window  BADGING / STRIPES  Challenger  R/T  SRT8®  Hemi® badge  SRT® Stripe Kit  R/T hood to fender stripes	S	TERIO S S S S	<b>R</b> }  S  S  S
Anti-spin differential rear axel (with manual transmission on R/T)  ANTENNA Integrated into rear window  BADGING / STRIPES  Challenger  R/T  SRT8®  Hemi® badge  SRT® Stripe Kit  R/T hood to fender stripes  6.1L HEMI® badge	S	TERIO S S S S	<b>R</b> }  S  S  S
Anti-spin differential rear axel (with manual transmission on R/T)  ANTENNA Integrated into rear window  BADGING / STRIPES  Challenger  R/T  SRT8®  Hemi® badge  SRT® Stripe Kit  R/T hood to fender stripes  6.1L HEMI® badge  EXHAUST SYSTEM  Stainless steel exhaust with single tip  Stainless steel performance exhaust with dual bright exhaust tips	S	TERIO S S S S	<b>R</b> }  S  S  S
Anti-spin differential rear axel (with manual transmission on R/T)  ANTENNA Integrated into rear window  BADGING / STRIPES  Challenger  R/T  SRT8®  Hemi® badge  SRT® Stripe Kit  R/T hood to fender stripes  6.1L HEMI® badge  EXHAUST SYSTEM  Stainless steel exhaust with single tip	S	S S S	<b>R</b> }  S  S  S
Anti-spin differential rear axel (with manual transmission on R/T)  ANTENNA Integrated into rear window  BADGING / STRIPES  Challenger  R/T  SRT8®  Hemi® badge  SRT® Stripe Kit  R/T hood to fender stripes  6.1L HEMI® badge  EXHAUST SYSTEM  Stainless steel exhaust with single tip  Stainless steel performance exhaust with dual bright exhaust tips	S	S S S	R }  s  s  s
Anti-spin differential rear axel (with manual transmission on R/T)  ANTENNA Integrated into rear window  BADGING / STRIPES  Challenger  R/T  SRT8®  Hemi® badge  SRT® Stripe Kit  R/T hood to fender stripes  6.1L HEMI® badge  EXHAUST SYSTEM  Stainless steel exhaust with single tip  Stainless steel performance exhaust with dual bright exhaust tips  Stainless steel high-performance exhaust with dual bright exhaust tips	S	S S S	R }  s  s  s
Anti-spin differential rear axel (with manual transmission on R/T)  ANTENNA Integrated into rear window  BADGING / STRIPES  Challenger  R/T  SRT8®  Hemi® badge  SRT® Stripe Kit  R/T hood to fender stripes  6.1L HEMI® badge  EXHAUST SYSTEM  Stainless steel exhaust with single tip  Stainless steel performance exhaust with dual bright exhaust tips  FUEL FILLER DOOR	S	S S S	R }  s  s  s
Anti-spin differential rear axel (with manual transmission on R/T)  ANTENNA Integrated into rear window  BADGING / STRIPES  Challenger  R/T  SRT8®  Hemi® badge  SRT® Stripe Kit  R/T hood to fender stripes  6.1L HEMI® badge  EXHAUST SYSTEM  Stainless steel exhaust with single tip  Stainless steel performance exhaust with dual bright exhaust tips  Stainless steel high-performance exhaust with dual bright exhaust tips  FUEL FILLER DOOR  Painted	S	S S S	R }  S  S  S  S  S

2009 GHALLENGER

216

EXTERIOR } CONT.	SE	R/T	SRT8®
<ul> <li>Xenon High Intensity Discharge headlamps</li> <li>Optional with Popular Equipment Package J on R/T</li> </ul>	S	S	
Automatic Included in Popular Equipment Package J on R/T		0	S
■ Fog lamps Included in Popular Equipment Package G on SE		Р	S
▶ MIRRORS	Р	S	S
Power body-color, folding	S	S	
Power body-color, folding, heated		0	S
▶ REAR SPOILER			
■ Body color		S	
Black			S
► SUNROOF  Power with one touch open / close and vent feature	0	0	0
▶ TIRES			
P215/65R17 BSW all-season touring	S		
P225/60R18 BSW touring Included with Popular Equipment Package G on SE	Р		
P235/55R18 BSW AS performance		S	
P245/45ZR20, P255/45ZR20 performance			0
P245/45ZR20 BSW all-season performance Optional with Popular Equipment Package J on R/T		0	
P245/45ZR20 all-season performance			S
TIREFIT System: tire sealant and electric compressor	S	S	S
Compact spare tire Optional with Popular Equipment Package G on SE and J on R/T	0	0	
▶ WHEELS			
■ 17"" Steel with bolt on wheel covers	S		
18" Aluminum Included in Popular Equipment Package G on SE	Р	S	
20" Aluminum Chrome-clad		0	
■ 20" SRT® Forged, polished aluminum			S
	{ INT	ERIOR	}
► AIR CONDITIONING			
Manual temperature control	S	S	S

			•
► AIR CONDITIONING			
Manual temperature control	S	S	S
CONSOLE TrunkFloor, with fore and aft slide, cell phone storage, front and rear climate control outlets and 12V power assessory delay	S	S	S
▶ DOOR LOCKS			
Power, speed-sensitive locking, child-protection rear	S	S	S
▶ ELECTRONIC VEHICLE INFORMATION CENTER (EVIC) Reconfigurable driver-interactive up to 128-function information display with steering wheel mounted controls (Included with Electronic Convenience Group)	S	S	S
▶ FLOOR MATS			
Front and rear		Р	ST
Luxury, front and rear Included in Popular Equipment Package G on SE	S		

316

{ INTERIOR } CONT.	SE	R/T	SRT8®
► HOMELINK® UNIVERSAL TRANSCEIVER  Programmable, 3-function with remote controls for garage door opener, interior/exterior home lighting or security devices (Included with Electronic Convenience Group)	Р	S	S
► KEYLESS GO™ Push button starter			S
► LIGHTING			
Front map lamps for reading and rear courtesy lamps	S	S	S
Trunk lamp	S	S	S
▶ MIRRORS			
Rearview, day / night	S	S	S
Rearview, auto dimming included with UConnect® hands-free communication system and security alarm	Р	Р	Р
▶ PEDALS  Non-adjustable	S	S	S
► POWER ACCESSORY  12V auxiliary power outlet located in center console	S	S	S
▶ REMOTE KEYLESS / ILLUMINATED ENTRY SYSTEM Includes two transmitters	S	S	S
▶ SHIFT KNOB			
Urethane	S		
Leather wrapped Included in Popular Equipment Package G on SE	Р	S	S
▶ SPEEDOMETER			
■ 140 mph with electroluminescent display, with tachometer	S	S	
■ 180 mph with electroluminescent display, with tachometer			S
► STEERING COLUMN  Tilt / telescoping, manual	S	S	S
▶ STEERING WHEEL			
Urethane	S		
■ Leather wrapped		S	S
Steering wheel mounted audio and EVIC controls if equipped Included in Electronics Convenience Group		Р	Р
► TEMPERATURE DISPLAY  Outside, located in instrument cluster (Included in Electronic Convenience Group)		Р	S

# { SEATING }

► FABRIC			
Cloth	S	S	
Leather trim Included with Leather Interior Group on SE and included with Popular Equipment Package J on R/T	O/P	Р	
Preminum Leather trim			S
Light Slate Gray inserts, must have Dk. Slate leather	0	0	
▶ FRONT	S	S	S
Front low-back buckets			
8-way power driver's seat	0	S	S
Heated front seats Included with Leather Interior Group			S
Manual driver / passenger adjustable lumbar	S	S	S

# { ENTERTAINMENT }

SRT8®

SE

		•	
▶ RADIOS			
■ AM/FM radio with CD and MP3 capability	S	S	S
■ AM/FM radio with integrated 6-disc CD changer with MP3 capability Included with Sound Group, Sound Group II, and SRT Option Group II	O/P	Р	Р
■ AM/FM radio with CD changer, MP3 capability, with DVD-based GPS navigation system with 5.8 inch display screen and UConnect® hands-free communication system, Universal Consumer Interface (UCI), and real time traffic updates Optional with Popular Equipment Package G on SE	0	0	Ο
SIRIUS® SATELLITE RADIO <i>(Included in Sound Group)</i>	0	0	S
▶ SOUND SYSTEMS			
Four speakers	S	S	
Six Boston Acoustics® speakers with 276-watt digital amplifier (Included with Sound Group)	Р	Р	S
Seven Boston Acoustics® speakers with 368-watt digital amplifier (Included with Sound Group II)		Р	
13 SRT High-Performance KICKER® speakers (eight locations) with a 322-watt digital amplifier and 200-watt subwoofer amplifier ( <i>Included with SRT Group II</i> )			Р
		•	

# { SAFETY & SECURITY }

Advanced multistage for driver and front-passenger	S	S	S
Supplemental side-curtain for front and rear outboard occupants	S	S	S
► CHILD SEAT ANCHOR SYSTEM (LATCH)			
Mounts for two child seats in the rear help ease the installation of compatible aftermarket child seats	S	S	S
► ELECTRONIC STABILITY PROGRAM <sup>(2)</sup>			
■ Includes Brake Assist  Included in Popular Equipment Package G on SE	Р	S	S
▶ SEAT BELTS  Height-adjustable 3-point driver and front-passenger with traveling buckles and seat belt pretensioners; 3-point lap / shoulder belts at all rear-seat positions	S	S	S
▶ SECURITY ALARM  Included in Electronic Convenience Group and SRT® Option Group 1		Р	Р
▶ SENTRY KEY®  Antitheft engine immobilizer	S	S	S
▶ TIRE PRESSURE MONITORING WARNING LAMP	S	S	
TIRE PRESSURE MONITORING DISPLAY Included in Electronic Convenience Grup		Р	S
▶ UCONNECT® HANDS-FREE COMMUNICATION SYSTEM			
Includes auto dimming rear view mirror  Included with SRT® Option Group I and Electronic Convenience Group		O/P	Р

## { PACKAGES }

▶ POPULAR EQUIPMENT PACKAGE G	0		
■ Includes antilock brakes, Electronic Stability Program with Traction Control and Brake Assist, 18" Aluminum Wheels, 8-way Power driver's Control, Fog Lamps, Luxury Floor Mats, Leather Wrapped Steering Wheel and Shift Knob, Security Alarm, Dual Illuminated Visor Mirrors			
POPULAR EQUIPMENT PACKAGE J		0	
■ Includes leather interior, Boston Acoustics® six speaker system with 276 watt ampllifier, SIRIUS Satellite Radio, heated front seats, luxury floor mats, Keyless Go <sup>™</sup> , seatback map pocket, automatic headlamps, heated outside mirrors			
▶ SOUND GROUP	0	0	
■ Includes AM/FM 6 Disc DVD and MP3 capability, 6 Boston Acoustic speakers, 276-watt amplifier and (SIRIUS Satellite Radio on 26G CPOS)			
▶ ELECTRONICS CONVENIENCE GROUP		0	0
■ Includes illuminated cupholders, rear view autodimming mirror with microphone, instrument cluster with display, temperture & compass with mini trip computer, illuminated door pulls, security alarm, UConnect® hands free communication, steering wheel mounted audio controls, Universal Garage door opener, remote start (automatic only), tire pressure monitoring display, and Universal Consumer Interface (UCI) (Requires Popular Equipment Package J on R/T)			
▶ LEATHER INTERIOR GROUP	0		
■ Includes Leather trimmed bucket seats, and heated front seats  Optional with Popular Equipment Package G on SE			
▶ SOUND GROUP II		0	
■ Includes AM/FM 6 Disc DVD and MP3 capability, seven Boston Acoustic® speakers and 368-watt amplifier Requires Popular Equipment Package J on R/T			
▶ SRT OPTION GROUP 1			0
■ Includes illuminated cup holders, Auto dimming rear view mirror with microphone, Security alarm, illuminated door pulls, Uconnect® hands-free communication system, remote start (automatic only), and Universal Consumer Interface (UCI)			
► SRT OPTION GROUP II			0
■ Includes AM/FM 6 Disc DVD and MP3 capability, 13 Kicker SRT high performance audio speakers, 322 watt KICKER® SRT® amplifier and 200 watt KICKER® SRT® subwoofer			
► TRAK PAK		Р	Р

■ Includes 6-speed manual transmission, Hill Start Assist, anti-spin differential (3.73 w/18", 3.92 w/20' wheels), ESC shutoff switch, and bright pedals (*Packaged with the manual transmission*)

 $\label{eq:local_local_local} \textit{I} = \textit{Included. P} = \textit{Available within package noted. O} = \textit{Optional, L} = \textit{Limited Production Option (Fleet Only), U} = \textit{Upgrade.}$ 

 ${\it (1) Always sit\ properly\ in\ the\ seat\ with\ the\ seat\ belt\ fastened.}$ 

(2) Always drive carefully, consistent with conditions. Always wear your seat belt and obey traffic rules.

AutoStick, SRT8, HEMI, Sentry Key, and Uconnect are registered trademarks of Chrysler LLC.

Bluetooth is a registered trademark of Bluetooth SIG, Inc.

Boston Acoustics is a registered trademark of Boston Acoustics, Inc.

HomeLink is a registered trademark owned by Johnson Controls, Inc.

KICKER @is a registered trademark of Stillwater Designs and Audio, Inc.

Brembo is a registered tradmark of Bembo SPA.

Keyless Go is a tradmark of Daimler AG.

#### STANDARD AND OPTIONAL FEATURE GROUPS

S = Standard P = Available within package or group noted in parentheses

O = Optional O/P = Item is a free-standing option and also included in a package or group

	SE	R/T	SRT8®
Engines and Transmissions			
3.5-L SOHC High Output V-6 with four-speed automatic transmission	S		
5.7-L HEMI® V-8 with six-speed manual transmission includes <b>TRACK PAK</b> Hill Start Assist (HSA), anti-spin rear axle, bright pedal covers, performance steering, ESP full-off switch		0	
5.7-L HEMI Multi-Displacement V-8 with five-speed automatic transmission with Auto Stick		S	
6.1-L SRT HEMI V-8 with six-speed manual transmission transmission includes <b>TRACK PAK</b> Hill Start Assist (HSA), anti-spin rear axle, bright pedal covers, performance steering, ESP full-off switch			0
6.1-L SRT HEMI V-8 with five-speed automatic transmission with Auto Stick			S

2009 DODGE CHALLENGER FEATURE AVAILABILITY 1

	SE	R/T	SRT8
Mechanical			
Alternator — 160-amp	S	S	S
Battery — 625-amp, maintenance free	S	S	S
Battery-saver feature — Enhanced, programmable to turn headlamps and other switched and non-switched interior lamps off after ignition is turned off	S	S	S
Brakes			
Four-wheel disc brakes	S		
Anti-lock four-wheel disc brakes and all-speed traction control (available in Popular Equipment Package G on SE)	Р	S	
High-performance four-wheel disc anti-lock with vented 14-inch front and 13.8-inch rear discs, includes Brembo Performance four-piston calipers and all-speed traction control			S
Engine block heater	0	0	
Engine cooling			
Heavy-duty	S	S	
Severe-duty II			S

2 FEATURE AVAILABILITY 2009 DODGE CHALLENGER

	SE	R/T	SRT8
Mechanical (cont.)			
Fuel tank			
18.5-gallon with tethered cap	S		
19-gallon with tethered cap		S	S
Speed control — Electronic with steering column-mounted controls	S	S	S
Steering			
Power rack-and-pinion	S		
Performance		S	
Performance-tuned			S
Suspension			
Touring	S		
Performance		S	
High-performance			S
Stablizer bar — Rear	S	S	S
Tip start — Prevents ignition from over cranking (N/A with manual transmission)	S	S	S
Axle — Anti-spin differential rear axle (with manual transmission on R/T)		S	S

2009 DODGE CHALLENGER FEATURE AVAILABILITY 3

	SE	R/T	SRT8
Exterior			
Antenna — Integrated into rear window	S	S	S
Badging and stripes			
Challenger	S	S	S
R/T		S	
SRT8			S
HEMI		S	
Hood stripe			0
R/T hood-to-fender stripes		0	
6.1-L HEMI			S
Doorhandles — Body color	S	S	S
Exhaust system			
Stainless steel exhaust with single tip	S		
Stainless steel performance exhaust with dual bright rectangular exhaust tips		S	
Stainless steel high-performance exhaust with dual bright rectangular exhaust tips			S

4 FEATURE AVAILABILITY 2009 DODGE CHALLENGER

	SE	R/T	SRT8
Exterior (cont.)			
Fuel filler door			
Painted	S		
Bright, polished aluminum		S	S
Grille — Satin chrome surrounded with black field	S	S	S
Glass — Solar control, all windows	S	S	S
Headlamps			
Halogen with delay	S	S	
Xenon High-intensity Discharge (HID) headlamps (optional with Popular Equipment Package J on R/T)		0	S
Automatic (included in Popular Equipment Package J on R/T)		Р	S
Fog lamps (included in Popular Equipment Package G on SE)	Р	S	S
Mirrors			
Power, body color, folding	S	S	
Power, body color, folding, heated (included in Popular Equipment Package J on R/T)		Р	S

2009 DODGE CHALLENGER FEATURE AVAILABILITY 5

	SE	R/T	SRT8
Exterior (cont.)			
Rear spoiler			
Body color		S	
Black			S
Sun roof — Power with one-touch open/close and vent feature (optional with Popular Equipment Package G on SE)	0	0	0
Tires			
P215/65R17 BSW all-season touring	S		
P225/60R18 BSW touring (included with Popular Equipment Package G on SE)	Р		
P235/55R18 BSW AS performance		S	
P245/45ZR20, P255/45ZR20 performance			0
P245/45ZR20 BSW all-season performance (optional with Popular Equipment Package J on R/T)		0	
P245/45ZR20 all-season performance			S
TIREFIT System: tire sealant and electric compressor	S	S	S
Compact spare tire (optional with Popular Equipment Package G on SE and J on R/T)	0	0	

6 FEATURE AVAILABILITY 2009 DODGE CHALLENGER

	SE	R/T	SRT8
Exterior (cont.)			
Wheels			
17-inch steel with bolt-on wheel covers	S		
18-inch aluminum (included in Popular Equipment Package G on SE)	Р	S	
20-inch aluminum chrome-clad		0	
20-inch SRT-exclusive, fully-forged, polished aluminum			S
Windows — Power front one-touch auto down	S	S	S
Windshield wipers — Two-speed with variable intermittent mode	S	S	S
Interior			
Air conditioning — Manual temperature control	S	S	S
Assist handles — Passenger	S	S	S
Cargo compartment dress-up — Trunk	S	S	S
Console — Floor, with fore and aft slide, cell phone storage, front and rear climate control outlets and 12-V power accessory delay	S	S	S
Defroster — Rear window	S	S	S

2009 DODGE CHALLENGER FEATURE AVAILABILITY 7

	SE	R/T	SRT8
Interior (cont.)			
Door locks — Power, speed-sensitive locking	S	S	S
Electronic Vehicle Information Center (EVIC) — Reconfigurable driver-interactive and information display with up to 128 functions and steering-wheel-mounted controls (included with Electronic Convenience Group)		Р	S
Floor covering — Carpet	S	S	S
Floor mats			
Front and rear	S		
Luxury, front and rear (included in Popular Equipment Package G on SE)	Р	S	S
HomeLink® universal transceiver — Programmable, three-function with remote controls for garage door opener, interior/exterior home lighting or security devices (included with Electronic Convenience Group)		Р	S
Interior accents — Satin silver lock knobs	S	S	S
Keyless Go — Push-button starter		Р	S

8 FEATURE AVAILABILITY 2009 DODGE CHALLENGER

	SE	R/T	SRT8
Interior (cont.)			
Lighting			
Front map lamps for reading and rear courtesy lamps	S	S	S
Trunk lamp	S	S	S
Mirrors			
Rearview, day/night	S	S	S
Rearview, auto dimming (included with UConnect® Hands-free Communication System and security alarm)	Р	Р	Р
Sun visor			
Driver and passenger visor with mirror	S		
Dual visor vanity, illuminated (included in Popular Equipment Package G on SE)	Р	S	S
Pedals — Non-adjustable	S	S	S
Power accessory — Twelve-volt auxiliary power outlet located in center console	S	S	S
Remote keyless/illuminated entry system — Includes two transmitters	S	S	S
Remote Start — Automatic transmission only		Р	Р

2009 DODGE CHALLENGER FEATURE AVAILABILITY 9

	SE	R/T	SRT8
Interior (cont.)			
Shift knob			
Urethane	S		
Leather-wrapped (included in Popular Equipment Package G on SE)	Р	S	S
Speedometer			
140 miles-per-hour with electroluminescent display and tachometer	S		
160 miles-per-hour with electroluminescent display and tachometer		S	
180 miles-per-hour with electroluminescent display and tachometer			S
Steering column — Tilt/telescoping, manual	S	S	S
Steering wheel			
Urethane	S		
Leather-wrapped		S	S
Steering wheel-mounted audio and EVIC controls, if equipped (included in Electronics Convenience Group)		Р	S
Temperature display — Outside, located in instrument cluster (included in Electronics Convenience Group)		Р	S

10 FEATURE AVAILABILITY 2009 DODGE CHALLENGER

	SE	R/T	SRT8
Seating			
Fabric			
Cloth	S	S	
Leather-trim (included with Leather Interior Group on SE and included with Popular Equipment Package J on R/T)	O/P	Р	
SRT-exclusive premium leather-trim			S
Light Slate Gray inserts (Dark Slate leather required)	0	0	
Front			
Front low-back buckets	S	S	S
Eight-way power driver's seat	O	S	S
Heated front seats (included with Leather Interior Group)	Р	Р	S
Manual driver/passenger adjustable lumbar	S	S	S
Rear			
60/40 split-folding rear bench with arm rest and two cup holders	S	S	S

2009 DODGE CHALLENGER FEATURE AVAILABILITY 11

	SE	R/T	SRT8
Entertainment			
Radios			
AM/FM radio with CD and MP3 capability	S	S	S
AM/FM radio with integrated six-disc CD changer with MP3 capability (included with Sound Group, Sound Group II, and SRT Option Group II)	O/P	Р	Р
AM/FM radio with CD changer, MP3 capability, with DVD-based GPS navigation system with 5.8-inch display screen and Uconnect Hands-free Communication System, Universal Consumer Interface (UCI), and real time traffic updates (optional with Popular Equipment Package G on SE)	0	0	0
SIRIUS® Satellite Radio (included in Sound Group)	О	0	S
Sound systems			
Four speakers	S	S	
Six Boston Acoustics® speakers with 276-watt digital amplifier (included with Sound Group)	Р	Р	S
Seven Boston Acoustics speakers with 368-watt digital amplifier (included with Sound Group II)		Р	
Thirteen SRT high-performance KICKER® speakers (eight locations) with a 322-watt digital amplifier and 200-watt subwoofer amplifier (included with SRT Group II)			Р

12 FEATURE AVAILABILITY 2009 DODGE CHALLENGER

	SE	R/T	SRT8
Safety and Security			
Air bags <sup>1</sup>			
Advanced multi-stage for driver and front-passenger	S	S	S
Supplemental side-curtain for front and rear outboard occupants	S	S	S
Child Seat Anchor System (LATCH) — Mounts for two child seats in the rear help ease the installation of compatible aftermarket child seats	S	S	S
Electronic Stability Program (ESP) <sup>2</sup> — Includes brake assist (included in Popular Equipment Package G on SE)	Р	S	S
Seat belts — Three-point driver and front-passenger with traveling buckles and seat belt pretensioners; three-point lap/shoulder belts at all rear-seat positions	S	S	S
Security alarm (included in Electronic Convenience Group and SRT Option Group 1)		Р	Р
Sentry Key® — Anti-theft engine immobilizer	S	S	S
Tire pressure monitoring warning lamp	S	S	

<sup>&</sup>lt;sup>1</sup> Always sit properly in the seat with the seat belt fastened. Children 12 and under should always be in a backseat correctly using an infant or child restraint system, or the seat belt positioned correctly for the child's age and weight.

2009 DODGE CHALLENGER FEATURE AVAILABILITY 13

<sup>&</sup>lt;sup>2</sup> No system, no matter how sophisticated, can repeal the laws of physics or overcome careless driving actions. Performance is limited by available traction, which snow, ice and other conditions can affect. When the ESP warning lamp in the speedometer flashes, the driver needs to use less throttle and adapt speed and driving behavior to prevailing road conditions. Always drive carefully, consistent with conditions. Always wear your seat belt.

	SE	R/T	SRT8
Safety and Security (cont.)			
Tire pressure monitoring display (included in Electronic Convenience Group)		Р	S
Uconnect Hands-free Communication System — Includes auto-dimming rear-view mirror (included with SRT Option Group I; Electronic Convenience Group and Navigation Equipped Radio)		O/P	Р
Packages			
<b>Popular Equipment Package G</b> — Includes anti-lock brakes, Electronic Stability Program (ESP) with traction control and brake assist, 18-inch aluminum wheels, eight-way power driver's seat, fog lamps, luxury floor mats, leather-wrapped steering wheel and shift knob, security alarm, dual-illuminated visor mirrors	0		
<b>Popular Equipment Package J</b> — Includes leather interior, Boston Acoustics six-speaker system with 276-watt ampllifier, SIRIUS Satellite Radio, heated front seats, luxury floor mats, Keyless Go, seatback map pocket, automatic headlamps, heated outside mirrors		0	
Sound Group I — Includes AM/FM six-disc DVD and MP3 capability, six Boston Acoustic speakers, 276-watt amplifier (and optional SIRIUS Satellite Radio)	0	0	
Sound Group II — Includes AM/FM six-disc DVD and MP3 capability, seven Boston Acoustic speakers and 368-watt amplifier (requires Popular Equipment Package J on R/T)		0	

14 FEATURE AVAILABILITY 2009 DODGE CHALLENGER

	SE	R/T	SRT8
Packages (cont.)			
Electronics Convenience Group — Includes illuminated cupholders, rear view auto-dimming mirror with microphone, instrument cluster with display, temperature and compass with mini trip computer, illuminated door handles, security alarm, Uconnect Hands-free Communication System, steering wheel-mounted audio controls, universal garage door opener, Remote Start (automatic only), tire pressure monitoring display, and Universal Consumer Interface (UCI) (requires Popular Equipment Package J on R/T)		0	
<b>Leather Interior Group</b> — Includes leather-trimmed bucket seats and heated front seats (optional with Popular Equipment Package G on SE)	0		
R/T Group — Includes functional hood scoop, Challenger script badge, body side stripe and 20-inch aluminum chrome-clad wheels		0	
SRT Option Group I — Includes illuminated cupholders, auto dimming rear view mirror with microphone, security alarm, illuminated door handles, Uconnect Hands-free Communication System, Remote Start (automatic only) and Universal Consumer Interface (UCI)			0
SRT Option Group II — Includes AM/FM six-disc DVD and MP3 capability, 13 KICKER SRT high-performance audio speakers, 322-watt KICKER SRT amplifier and 200-watt KICKER SRT subwoofer			0
<b>Track Pak</b> — Includes six-speed manual transmission, Hill Start Assist, anti-spin differential (3.73 w/18-inch, 3.92 w/20-inch wheels), ESP full-off switch and bright pedals (packaged with the manual transmission)		Р	Р

2009 DODGE CHALLENGER FEATURE AVAILABILITY 15

#### **VEHICLE SPECIFICATIONS**

Specifications are based on the latest product information available at the time of publication. All dimensions are in inches (millimeters) unless otherwise noted. All dimensions measured at curb weight with standard tires and wheels.

#### **General Information**

Body-style	. Coupe
Assembly Plant	. Brampton, Ontario, Canada
EPA Vehicle Class	. Intermediate Car
Introduction Date	. September 2008

#### Engine: 6.1-liter HEMI® V-8

Availability	SRT8®
Type and Description	90-degree V-type, liquid-cooled
Displacement	370 cu. in. (6059 cu. cm)
Bore x Stroke	. 4.06 x 3.58 (103.0 x 90.9)
Valve System	
	all with roller followers

2009 DODGE CHALLENGER SPECIFICATIONS 1

#### Engine: 6.1-liter HEMI V-8 (cont.)

Fuel Injection	Sequential, multi-port, electronic, returnless
Construction	Deep-skirt cast-iron block with cross-bolted main bearing caps, aluminum alloy heads with hemispherical combustion chambers
Compression Ratio	10.3:1
Power (estimated SAE net)	425 hp (317 kW) @ 6200 rpm (69.8 hp/L)
Torque (estimated SAE net)	420 lbft. (569 N•m) @ 4800 rpm
Maximum Engine Speed	6400 rpm (electronically limited)
Fuel Requirement	Recommended: unleaded premium, 91 octane (R+M)/2
Oil Capacity	7 qt. (6.6-L)
Coolant Capacity	14 qt. (13.25-L)
Emission Controls	Dual close-coupled three-way catalytic converters; quad heated oxygen sensors and internal engine features <sup>a</sup>
Maximum Gross Trailer Weight	Not recommended
Estimated EPA Fuel Economy, mpg (city/hwy)	(TBD) automatic (TBD) manual

2 SPECIFICATIONS 2009 DODGE CHALLENGER

<sup>&</sup>lt;sup>a</sup> Meets Federal Tier 2, Bin 5 emissions requirements; marketed in California as an LEVII (Low Emission Vehicle) under cleanest vehicle rules.

#### Engine: 5.7-liter HEMI V-8

Availability	R/T
Type and Description	90-degree V-type, liquid-cooled with variable-valve timing
Displacement	345 cu. in. (5654 cu. cm)
Bore x Stroke	3.92 x 3.58 (99.5 x 90.9)
Valve System	16 pushrod-operated overhead valves, with variable-valve timing, conventional hydraulic lifters, all with roller followers
Fuel Injection	Sequential, multi-port, electronic, returnless
Construction	Deep-skirt cast-iron block with cross-bolted main bearing caps, aluminum alloy heads with hemispherical combustion chambers
Compression Ratio	10.5:1
For Automatic Transmission	
Power (estimated SAE net)	370 hp (276 kW) @ 5800 rpm (65.4 hp/L) <sup>b</sup>
Torque (estimated SAE net)	398 lbft. (540 N•m) @ 4200 rpmb
Fuel Requirement	Recommended: unleaded mid-grade, 89 octane (R+M)/2 Acceptable: unleaded regular, 87 octane (R+M)/2

<sup>&</sup>lt;sup>b</sup> Official SAE certified results per J2723 available in May 2008.

2009 DODGE CHALLENGER SPECIFICATIONS 3

#### Engine: 5.7-liter HEMI V-8 (cont.)

#### **For Manual Transmission**

Power (estimated SAE net)	375 hp (280 kW) @ 5800 rpm (66.3 hp/L)°
Torque (estimated SAE net)	404 lbft. (548 N•m) @ 4200 rpm <sup>c</sup>
Fuel Requirement	
	Acceptable: unleaded regular, 87 octane (R+M)/2
Maximum Engine Speed	5800 rpm (electronically limited)
Oil Capacity	7 qt. (6.6-L)
Coolant Capacity	14.7 qt. (13.9-L)
Emission Controls	Dual close-coupled three-way catalytic converters, quad heated oxygen sensors and internal engine features <sup>d</sup>
Maximum Gross Trailer Weight	1000 lbs. (453.6 kg) automatic (not recommended with manual)
Estimated EPA Fuel Economy, mpg (city/hwy)	16/23 automatic 15/23 manual

 $<sup>^{\</sup>circ}$  Official SAE certified results per J2723 available in May 2008.

<sup>&</sup>lt;sup>d</sup> Manual transmission meets Federal Tier 2, Bin 5 emissions requirements; marketed in California as an LEVII (Low Emission Vehicle) under cleanest vehicle rules. Automatic transmission meets Federal Tier 2, Bin 4 emissions requirements; marketed in California as an ULEVII (Ultra Low Emission Vehicle) under cleanest vehicle rules.

## Engine: 3.5-liter High Output SOHC 24-valve V-6

Availability	SE
Type and Description	60-degree bank angle, liquid-cooled, three-plenum intake manifold with electronic short-runner valves
Displacement	214.7 cu. in. (3518 cu. cm)
Bore x Stroke	3.78 x 3.19 (96 x 81)
Valve System	SOHC, 24-valve, hydraulic, center pivot roller rocker arms
Fuel Injection	Sequential, multi-port, electronic
Construction	Precision sand-cast mold aluminum block with cast-in-iron liners, cross-bolted main bearing caps and cast-aluminum heads
Compression Ratio	10.0:1
Power (estimated SAE net)	250 hp (186 kW) @ 6400 rpm (71.1 hp/L)

#### Engine: 3.5-liter High Output SOHC 24-valve V-6 (cont.)

Torque (SAE net, estimated)	250 lbft. (339 N•m) @ 3800 rpm
Maximum Engine Speed	6800 rpm (electronically limited)
Fuel Requirement	Recommended: unleaded mid-grade, 89 octane (R+M)/2 Acceptable: unleaded regular, 87 octane (R+M)/2
Oil Capacity	6 qt. (5.7-L) with dry filter
Coolant Capacity	10.8 qt. (10.2-L)
Emission Controls	Dual close-coupled three-way catalytic converters, quad heated oxygen sensors and internal engine features <sup>e</sup>
Maximum Gross Trailer Weight	1000 lbs. (453.6 kg)
Estimated EPA Fuel Economy, mpg (city/hwy)	18/25

<sup>&</sup>lt;sup>e</sup> Meets Federal Tier 2, Bin 5 emissions requirements; marketed in California as a ULEVII (Low Emission Vehicle) under cleanest vehicle rules.

#### Transmission: Automatic, Four-speed Overdrive (42RLE)

Availability	3.5-L SE
Description	
Gear Ratios	
1st	2.84
2nd	1.57
3rd	1.00
4th	0.69
Reverse	2.21
Final Drive Ratio	3.64
Overall Top Gear Ratio	2.51

2009 DODGE CHALLENGER SPECIFICATIONS 7

#### Transmission: Automatic, Five-speed Overdrive

Availability	5.7-L R/T and 6.1-L SRT8
Description	Adaptive electronic control with Auto Stick driver-interactive manual control and electronically modulated torque converter clutch
Gear Ratios	
1st	3.59
2nd	2.19
3rd	1.41
4th	1.00
5th	0.83
Reverse	3.16
Final Drive Ratio	5.7-L — 3.06
	6.1-L — 3.06
	Getrag axle with limited slip differential (6.1-L only)
Overall Top Gear	5.7-L — 2.54
	6.1-L — 2.54
	Getrag axle with limited slip differential (6.1-L only)

# Transmission: Six-speed Manual Tremec TR-6060 Transmission Clutch: ZF-Sachs 250 mm Twin Disc

Availability Optional — 5.7-L R/T and 6.1-L SRT8	
Description	Triple cone / double cone synchronizer design, 1–4 skip shift and reverse inhibit solenoids, 5:1 remote shifter
Gear Ratios	
1st	2.97
2nd	2.10
3rd	1.46
4th	1.00
5th	0.74
6th	0.50
Reverse	2.90
Final Drive Ratio	5.7-L — 3.73 (18-inch wheels)
	5.7-L — 3.91 (20-inch wheels)
	6.1-L — 3.91
	Getrag axle with limited slip differential (5.7-L and 6.1-L)

#### **Electrical System**

Alternator	. 160A
Battery	. H7 Case, 625 CCA, maintenance free

#### **Dimensions and Capacities**<sup>f</sup>

Wheelbase	116.0 (2946)
Track, Front	63.0 (1603)
Track, Rear	63.1 (1604)
Overall Length	197.7 (5023)
Overall Width	75.7 (1923)
Overall Height	57.1 (1449)
Ground Clearance	SRT8 @ curb 4.8 (122.2) (R/T and SE — TBD)
Frontal Area	25.3 sq. ft. (2.35 sq. m)

<sup>&</sup>lt;sup>f</sup> All dimensions measured at curb weight with standard tires.

#### **Dimensions and Capacities** (cont.)

Drag Coefficient	SE — 17-inch and 18-inch tires — 0.350 (8.86 CdA)
	${ m R/T-18-inch-0.350~(8.73~CdA);}\ 20-inch-0.355~(8.98~CdA)$
	SRT8 — 0.353 (9.01 CdA)
Curb Weight (estimated)	SE — 3720 lbs. (1688 kg)
	R/T — 4041 lbs. (1833 kg)
	SRT8 — 4170 lbs. (1892 kg)
Weight Distribution (percent front/rear)	SE — 53.5/46.5
	R/T — 54.7/45.3
	SRT8 — 55.6/44.4
Fuel Tank Capacity	SE — 18 gal. (68.1-L)
	R/T and SRT8 — 19 gal. (71.9-L)

#### **Accommodations**

Seating Capacity (front/rear)	2/3
Front	
Head Room	39.3 (999)
Leg Room	42.0 (1067)
Shoulder Room	58.2 (1477)
Hip Room	54.6 (1387)
Seat Travel	Driver — 10.6 (270)  Passenger — 8.7 (220)
Recliner Angle Range	Driver — 64 deg. Passenger — 63 deg.
SAE Front Volume Index	55.8 cu. ft. (1.58 cu. m)

#### **Accommodations** (cont.)

#### Rear

Head Room	37.4 (950)
Leg Room	32.6 (829)
Knee Clearance	
Shoulder Room	53.9 (1368)
Hip Room	48.6 (1236)
SAE Rear Seat Volume Index	38.1 cu. ft. (1.08 cu. m)
Total Interior Volume	91.5 cu. ft. (2.59 cu. m)
SAE Cargo Volume (same as Charger)	16.2 cu. ft. (0.459 cu. m)
EPA Interior Volume Index	
Trunk Liftover Height	33.0 (839)

#### Body

Layout	Longitudinal front engine, rear-wheel drive
·	
Construction	Unitized steel body

#### **Exhaust**

Type	SE — Single exhaust
	R/T and SRT8 — Dual exhaust with rectangular bright tip
	and image sound

#### Steering

Type	Rack-and-pinion with hydraulic power assist
Overall Ratio	16.1:1
Turning Diameter (curb-to-curb)	SE and R/T — 38.9 ft. (11.9 m) SRT8 — 37.5 ft. (11.48 m)
Steering Turns (lock-to-lock)	2.75
P/S Pump	Fixed displacement, speed-sensitive — Standard on automatic transmissions and SRT8 manual transmission  Variable Displacement — R/T manual transmission only

#### Suspension

#### SRT8

Front	Independent SLA with high upper "A" arm, coil spring over Bilstein monotube gas-charged shock absorbers and stabilizer bar; lateral and diagonal lower links
Rear	Five-link independent with coil springs, link-type stabilizer bar, Bilstein monotube gas-charged shock absorbers and isolated suspension cradle
R/T and SE	
Front	Independent SLA with high upper "A" arm, coil spring over gas-charged shock absorbers and stabilizer bar; lateral and diagonal lower links
Rear	Five-link independent with coil springs, link-type stabilizer bar, gas-charged twin tube shock absorbers and isolated suspension

2009 DODGE CHALLENGER SPECIFICATIONS 15

#### Tires<sup>g</sup>

#### SRT8

Availability	Standard
Size and Type	P245/45ZR20 all-season performance
Manufacturer and Model	Goodyear RSA
Revs per Mile (km)	731 (456)
Availability	Optional
Size and Type	P245/45ZR20 front P255/45ZR20 rear three-season tires
Manufacturer and Model	Goodyear F1 Supercar
Revs per Mile (km)	726 (450) front/718 (445) rear
R/T	
Availability	Standard
Size and Type	P235/55R18V 99V black sidewall all-season performance
Manufacturer and Model	Michelin MXM4
Revs per Mile (km)	729 (453)

 $<sup>\</sup>ensuremath{^{\mathrm{g}}}$  Other sizes and brands may also be used.

#### Tires (cont.)

Availability	Optional
Size and Type	P245/45ZR20 99V black sidewall all-season performance
Manufacturer and Model	Goodyear Eagle RSA
Revs per Mile (km)	731 (456)
SE	
Availability	Standard
Size and Type	P215/65R17 98T black sidewall all-season ride
Manufacturer and Model	Goodyear Integrity
Revs per Mile (km)	739 (459)
Availability	Standard with Popular Equipment Package
Size and Type	P225/60R18H 99H all-season touring
Manufacturer and Model	Continental ProContact
Revs per Mile (km)	729 (453)

2009 DODGE CHALLENGER SPECIFICATIONS 17

#### Wheels

#### SRT8

Availability	. Standard
Type and Material	. Fully-forged aluminum
Size	. 20 x 9.0
R/T	
Availability	. Standard
Type and Material	. Cast aluminum
Size	. 18 x 7.5
Availability	. Optional
Type and Material	. Cast aluminum
Size	. 20 x 8.0
SE	
Availability	. Standard
Type and Material	. Steel
Size	. 17 x 7.0

#### Wheels (cont.)

#### **Brakes**

#### SRT8

#### Front

2009 DODGE CHALLENGER SPECIFICATIONS 19

#### Brakes (cont.)

Four-Wheel Anti-Lock and Traction Control	Standard
Electronic Stability Control and Brake Assist	Standard
Brake Knockback Mitigation	Standard
Hill Start Assist	Standard with manual transmission
Power Assist Type	8 + 9 (203 + 209) tandem-diaphragm vacuum booster
R/T	
Front	
Rotor Size and Type	13.6 x 1.1 (345 x 28) vented
Caliper Size and Type	1.65 (42) dual piston sliding with aluminum housing
Swept Area	292 sq. in. (1884 sq. cm)
Rear	
Rotor Size and Type	12.6 x 0.4 (320 x 22) vented
Caliper Size and Type	1.65 (42) single piston sliding with aluminum housing
Swept Area	260.4 sq. in. (1680 sq. cm)
Four-Wheel Anti-Lock and Traction Control	Standard

20 SPECIFICATIONS 2009 DODGE CHALLENGER

#### Brakes (cont.)

Electronic Stability Control and Brake Assist	Standard
Hill Start Assist	Standard with manual transmission
Power Assist Type	8 + 9 (203 + 209) tandem diaphragm vacuum
SE	
Front	
Rotor Size and Type	12.6 x 1.1 (320 x 28) vented
Caliper Size and Type	2.365 (60) single piston sliding with aluminum housing
Swept Area	254.8 sq. in. (1644 sq. cm)
Rear	
Rotor Size and Type	12.6 x 0.4 (320 x 10) solid
Caliper Size and Type	1.65 (42) single piston sliding with aluminum housing
Swept Area	260.4 sq. in. (1680 sq. cm)
Four-Wheel Anti-Lock and Traction Control	Standard with Popular Equipment Package
Electronic Stability Control and Brake Assist	Standard with Popular Equipment Package

2009 DODGE CHALLENGER SPECIFICATIONS 21